#### Counter-Shutter Fire Door AIMPORTANT ALL GAPS, EDGES AND SEAMS MUST BE SEALED AROUND THE FULL PERIMETER OF THE DOOR WITH DOW RTV SILICONE 723 OR EQUAL. Hand Chain Operated SMOKE AUTO 🐽 Face of Wall Mounted Page#: Page 1 NOTE: Redi-Reset Hand Chain Only. For FM approved Fire - Right Guide door, flame baffle and - Bracket fusible link system is used GW - Guide Width GD - Guide Depth Fusible Link Fasten hood to wall Charge - Max. 10" o/c Wheel LG-[50.8] Perimeter Brush Seals Max. 12" o/c Hand chain [304.8] COW Clear Opening Width Slide Locks WALL COIL OGW Overall Guide Width OFW Overall Frame Width VERTICAL SECTION A - A COIL SIDE ELEVATION FACE MOUNTED TO MASONRY FACE MOUNTED TO STEEL Wall opening Wall opening width 1/2" width [38.10] 1 1/4" Brush Seals [50.8] [50.8] [31.75] 1/2" COW 1-1/4" baby flat slat [12.7] OGW OGW **CURTAIN DETAIL** GUIDE SECTION B - B ŞALEŞ REP: Manufactured by: Notes:

1. See page 2 for more options.

2. All metric conversions of dimensions are shown in brackets [].

SALES REP:

CUSTOMER:

JOB NAME:

NUMBER:

# Manufactured by: OVERHEAD DOORS, INC. 8 HULSE ROAD EAST SETAUKET, N.Y. 11733 TEL: (631)473-9300 FAX: (631)642-0800

© COPYRIGHT MAY 2007

## **Counter-Shutter Fire Door**


# 1 1/4" Baby Flat Slat




Hand Chain Operated Face of Wall mounted

Page#:


Page 2







### **BOTTOM BAR OPTIONS**

#### HOOD SHAPES AVAILABLE FOR THIS DOOR



#### **GUIDE DETAIL**






FM REQUIRES INTERMEDIATE SUPPORTS, NOT MORE THAN 8'-0" APART.

#### FLAME BAFFLE DETAIL

#### Distributed By:

Call your Alpine representative for additional options and safty products to help find the best. Alpine door to suit your needs.



# 1 1/4" Baby Flat Slat

NOTE: MAXIMUM PIPE **DEFLECTION ON ANY SIZE** 


**DOOR IS .034** 



Page#: Page 3

Finding the minimum required operation for the size door you need.

## Height of Shutter



## Operator Legend

- Hand Chain Operation Motor Operation Only


To use Chart: Find where your door width and height meet to find the minimum operation that

may be used for that door size.

For example: The blue line indicates a Hand Chain Operation. Any size door on that line or above that line may use a Hand Chain, including the door sizes that fall into the Manual push up door. But, The Manual push up door may not be used for any door size below the line representing Push up operation. For any door size larger than what is represented here please consult your Alpine Overhead Doors, Inc. Factory. This Graph is for reference only, subject to change without notice.

Finding the minimum required bracket size for the door you need.

## Height of Shutter



NOTE: Bracket sizes may vary based on gauge of curtain. Bracket size is directly related to the pipe low moment arm deflection (not more than .03 inches per foot).

To use Chart: Find where your door width and height meet to find the minimum bracket size for your door. For any door size larger than what is represented here please consult your Alpine Overhead Doors, Inc. Factory. This Graph is for reference only, subject to change without notice.

Distributed By:

