

Split-Frame[™] Features

- Integral frame shutter
- Fits into new & existing openings up to 12' x 8' maximum
- Customized to fit your wall thickness
- Accent and enhance building decor
- Available in a variety of finishes



Alpine's Split-Frame[™] integral frame doors are ideal for use office windows, cashier's windows, healthcare facilities and hospitals, parts windows, will call windows, medication dispensaries, check cashing windows, banks, and many more.

Functional Benefits

- These doors are fully assembled at the factory and offer a clean, custom appearance with no exposed edges
- No field assembly required therefore these doors make for a quick and easy installation
- Completed units are factory welded and provide a seamless, built-in look
- Units are built to exact opening size requirements

PIPE/BARREL ASSEMBLY

Steel pipe barrel carrying a curtain load with a maximum deflection of .03"/ft of door width

HOOD

Galvanized steel (standard)

CURTAIN

Interlocking 1.25" roll-formed flat slats in galvanized steel

INTEGRAL FRAME

Welded frame construction made up from 12/14 gauge steel

GUIDES

14 ga roll-formed steel mounting angles, (field welding required) and removable bellmouth curtain stops to allow for curtain maintenance without removal of guides, in Alpine Gray

BOTTOM BAR

Galvanized steel angles
Option: Single angle, or tubular

Operational Requirements

- Manual push up, hand crank, hand chain or motor operated. All operators can be adapted to specific conditions.

Optional Materials and Finishes

- Stainless Steel or Pre-Painted
- Exo-Shield™ powder coating
- Guides available in galvanized, gray primer or stainless steel finish

Product Selection Guide

More Economical

Better Performance

